

POWER DISTRIBUTION BOARD

VERTICAL - 39RU - 03209-62



Wired 20A AUS Outlet Round White 240V AC - 50Hz single phase

Metalwork assembled
 Front - 1.0mm Galvaneal Steel Powder Coat Black Sable
 Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	03209-62
Input Voltage	240V AC
Input Current (Phase)	20A
Max Input Power	4800 watts
Input Phases	Single Input
Input Type	AUS Outlet Screw Lock Plug 20A 3 Flat Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 20A Reset Overload Protection
Outlet Type	20A AUS Outlet (AS3112)
Outlet Quantity	18
Outlet Colour	White
Fittings Supplied	M5x10 screws and washers x4



Screw Lock Plug 20A 3 Flat Pin (AS3112)

DIMENSIONS	
Dimensions	1734mm L x 44mm W x 48mm D
Weight	2.6kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to website
Installed	Fitted to customer specified position in Server Rack

