

POWER DISTRIBUTION BOARD

VERTICAL - 18RU - 93500-156



PCB Mounted 15A AUS Outlet Socket 240V AC - 50Hz single phase

Metalwork assembled

Front - 1.0mm Galvaneal Steel Powder Coat Black Sable

Rear - Aluminium Extrusion - Black Anodised

| SPECIFICATIONS | |
|-----------------------|---|
| Part No | 93500-156 |
| Input Voltage | 240V AC |
| Input Current (Phase) | 15A |
| Max Input Power | 3600 watts |
| Input Phases | Single Input |
| Input Type | AUS Outlet Screw Lock Plug 15A 3 Flat Pin (AS3112) |
| Lead Length | 2.5M - Black |
| Control Function | Circuit Breaker 15A Reset Overload Protection |
| Outlet Type | 15A AUS Outlet (AS3112) |
| Outlet Quantity | 6 |
| Outlet Colour | Black |
| Fittings Supplied | M5x10 screws and washers x4 |



Screw Lock Plug 15A 3 Flat Pin (AS3112)

| DIMENSIONS | |
|------------------------|---|
| Dimensions | 800mm L x 44mm W x 48mm D |
| Weight | 1.3kgs |
| Country of Manufacture | Australia |
| Compliance | AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks |
| Packaging | Sealed Plastic Bag |
| Assembly Instructions | Refer to website |
| Installed | Fitted to customer specified position in Server Rack |

