



# S100 HD OPEN PATCHING FRAME

The S100 High Density Open Patching Frame offers a simple and flexible solution to high density structured cabling systems.

Providing an open environment for any cabling solution, and with the addition of 300mm wide ducting systems either side, the S100 is a perfect low cost solution for any large capacity secure cabling environment.

The 4 post frame is designed to be adjustable in depth and the 300mm wide cable ducts can be installed at the front, rear or both front and rear positions.

## FEATURES

<b>Rated Static Load Support</b>	800kg
<b>Flexibility</b>	Adjustable Depth Frame
<b>Expandability</b>	Frames can be bayed together
<b>Plinth</b>	Fitted as standard and includes bolt down provisions
<b>Fixing Provisions</b>	Located in top frame
<b>Cable Ducts</b>	300mm with support fingers
<b>Removable Duct Doors</b>	Fitted with a concealed hinge latching system that allows the user to open the door from either side, central operation of the latching system makes operation easy
<b>Duct Cable Entry</b>	Top, bottom and rear of each duct
<b>Vertical Mounting Rails</b>	19" racking to IEC60297
<b>Material</b>	High strength 2.0mm Galvaneal steel frame with pre-treatment

## FINISH

<b>Finish</b>	Powder Coated Black
---------------	---------------------

## SIZES

<b>Heights (RU)</b>	45
<b>Widths (mm)</b>	600
<b>Depths (mm)</b>	600 - 800



Cable duct showing door open and cable entry zones at rear