

## Product Guide

**A 2347** 5 Zone 40W Attenuator With Override Relays



# A 2347 5 Zone 40W Attenuator With Override Relays



### Overview

May be configured to either five single inputs to five outputs or one input to five outputs. Each zone has a 40W load capacity with a total panel capacity of 200W. All models have ten positions plus OFF. The input and outputs are connected via heavy duty screw terminals on the rear panel. Housed in a 2U rack panel and supplied with an engraving strip to label the speaker zones. Suits 100V systems only. All controllers include a 22µF bipolar capacitor for line monitoring purposes.

### About the override feature

It is often necessary to override the volume control in an evacuation control system during an emergency situation. A relay is used to bypass the attenuation circuitry enabling an announcement at full volume regardless of the volume setting, including off.

### Specifications

Power rating:	200W (40W per zone)
Relay override operation voltage:	24V DC
Dimensions:	484W x 50D x 88H mm
Weight:	2.3kg

### Key Features

- ✓ **Australian made**
- ✓ Standard 2 unit 19" rack mount
- ✓ 5 Zone outputs
- ✓ Accepts up to 5 inputs
- ✓ 10 positions plus an OFF for each zone
- ✓ 200W Total load capacity (40W per zone)
- ✓ Screw terminals for easy installation
- ✓ Override relays for bypassing volume settings

### About Redback® Public Address Products

**Redback® products are proudly designed, engineered and manufactured in Australia.**

Each unit is covered by a comprehensive 10 year parts and labour warranty. Redback® offers rock solid reliability from over 30 years experience in the commercial sound industry. Redback® offer locally available servicing and parts, plus the ability to offer feedback direct to the manufacturer.